

Material Safety Data Sheet



Date: 07/24/2007

Product: 19501030 - F200

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: Calgon Carbon Corporation

P.O. Box 717

Pittsburgh, PA 15230-0717

Emergency Phone Number: (412) 787-6700

Date Prepared: 6/24/2002

Prepared By: S. Liller

Chemical Name and Synonyms: Carbon

Formula: C

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Nonhazardous components are listed at 3% or greater; acute hazards are listed when present at 1% or greater and chronic hazards are listed when present at 0.01% or greater. This is not intended to be a complete compositional disclosure.

<u>INGREDIENT</u>	<u>% (BY WEIGHT)</u>	<u>CAS#</u>
CARBON	100	7440-44-0

SECTION III - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Black particulate solid, pellet or powder. Contact may cause eye irritation. Dust may be slightly irritating to eyes and respiratory tract.

CAUTION!! Wet activated carbon removes oxygen from air causing a severe hazard to workers inside carbon vessels and enclosed or confined spaces. Before entering such an area, sampling and work procedures for low oxygen levels should be taken to ensure ample oxygen availability, observing all local, state and federal regulations.

POTENTIAL HEALTH EFFECTS:

Effects and Hazards of Eye Contact: The physical nature of the product may produce eye irritation.

Effects and Hazards of Skin Contact: The product is not a primary skin irritant. The primary skin irritation index (Rabbit) is 0.

Effects and Hazards of Inhalation (Breathing): The product is practically non-toxic through inhalation. The acute inhalation LC₅₀ (Rat) is >64.4 mg/l (nominal concentration) for activated carbon.

Effects and Hazards of Ingestion (Swallowing): The product is non-toxic through ingestion. The acute oral LD₅₀ (RAT) is >10g/kg.

Primary Routes of Entry: Inhalation, ingestion, skin contact, eye contact.

Chronic Effects: The effects of long-term, low-level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposures.

CARCINOGENICITY: NTP: N/A IARC: N/A OSHA REGULATED: NO

Material Safety Data Sheet



SECTION IV - FIRST AID MEASURES

Treatment for Eye Contact: Flush with plenty of water for at least 15 minutes.
Treatment for Skin Contact: Wash with soap and water.
Treatment for Inhalation (Breathing): N/A
Treatment for Ingestion (Swallowing): N/A

SECTION V - FIRE FIGHTING MEASURES

Flash Point: N/A
Limits Lel: N/A
Uel: N/A
Extinguishing Media: FLOOD WITH PLENTY OF WATER.
Special Firefighting Procedures: NONE
Unusual Fire and Explosion Hazards: Contact with strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc., may result in fire.
NFPA RATING: HEALTH = 0 REACTIVITY = 0 FLAMMABILITY = 1

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled: Sweep up unused carbon and discard in refuse container or repackage.
Waste Disposal Method: Dispose of unused carbon in refuse container. Dispose of in accordance with local, state, and federal regulations.

SECTION VII - HANDLING AND STORAGE

Precautions for Handling and Storage: CAUTION!! Wet activated carbon removes oxygen from air causing a severe hazard to workers inside carbon vessels and enclosed or confined spaces. Before entering such an area, sampling and work procedures for low oxygen levels should be taken to ensure ample oxygen availability, observing all local, state, and federal or national regulations.
Other Precautions: Wash thoroughly after handling. Exercise caution in the storage and handling of all chemical substances.

Material Safety Data Sheet



SECTION VIII - EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure Guidelines:

OSHA PEL* 5 mg/M³ (Respirable)

ACGIH TLV* 10 mg/M³ (Total)

*PELs and TLVs are 8-hour TWAs unless otherwise noted.

Respiratory Protection: A NIOSH approved particulate filter respirator is recommended if excessive dust is generated.

Ventilation: Local Exhaust Ventilation: Recommended

Mechanical Ventilation: Recommended

Protective Gloves: Recommended

Eye Protection: Safety Glasses or Goggles Recommended

Other Protective Equipment: Not Required

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N/A

Specific Gravity: 2.3 g/cc real density

Vapor Pressure: N/A

Melting Point: N/A

Vapor Density: N/A

Evaporation Rate: N/A

Solubility in Water: NEGLIGIBLE

Packing Density: 0.4 to 0.7 g/cc

Appearance and Odor: Black particulate solid, pellet, or powder

SECTION X - STABILITY AND REACTIVITY

Stability: STABLE

Conditions to avoid: NONE

Incompatibility (Materials to avoid): Strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc.

Hazardous Decomposition Products: Carbon monoxide may be generated in the event of a fire.

Polymerizing Conditions to Avoid: NONE

SECTION XI - TOXICOLOGICAL INFORMATION

See HEALTH EFFECTS SECTION III

SECTION XII - ECOLOGICAL INFORMATION

Not determined

Material Safety Data Sheet



SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of unused carbon in refuse container. Dispose of in accordance with local, state, and federal or national regulations.

SECTION XIV - TRANSPORT INFORMATION

Proper Shipping Name: NOT REGULATED

Hazard Class: N/A

Identification Number: N/A

Packing Group: N/A

This product has been tested according to the United Nations *Transport of Dangerous Goods* test protocol for spontaneously combustible materials. It has been specifically determined that this product does not meet the definition of a self heating substance or any hazard class, and therefore is not a hazardous material and not regulated.

SECTION XV - REGULATORY INFORMATION

SARA TITLE III: N/A

TSCA: The ingredients of this product are on the TSCA Inventory List.

OSHA: Nonhazardous according to definitions of health hazard and physical hazard provided in the Hazard Communication Standard (29 CFR 1910.1200)

CANADA

WHMIS CLASSIFICATION: Not Classified

DSL#: 6798

EEC Council Directives relating to the classification, packaging and labeling of dangerous substances and preparations.

Risk (R) and Safety (S) phrases: May be irritating to eyes (R36).

SECTION XVI - OTHER INFORMATION

Intended Use: Generally used for treatment of liquids and gases.

While this information and recommendations set forth herein are believed to be accurate as of the date hereof, CALGON CARBON CORPORATION MAKES NO WARRANTY WITH RESPECT AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

*** END OF MATERIAL SAFETY DATA SHEET ***
